

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A strained silicon carbon alloy MOSFET structure, comprising:

a substrate;

a graded SiGe layer on the substrate;

a relaxed buffer layer on the graded SiGe layer;

a strained silicon carbon alloy layer on the relaxed buffer layer acting as a channel;

a gate dielectric layer on the strained silicon carbon alloy layer;

a ~~polysilicon~~ gate electrode on the gate dielectric layer; and

a source region and a drain region on the substrate opposite and adjacent to the ~~polysilicon~~ gate electrode.
2. (Original) The structure of claim 1, wherein the relaxed buffer layer comprises Si-Ge-C alloy, Si, Ge or other combinations of at least two semiconductor materials.
3. (Original) The structure of claim 1, wherein the gate dielectric layer comprises HfO₂, Si₃N₄, Al₂O₃, or any high dielectric constant (high k) dielectric material.
4. (Original) The structure of claim 1, wherein the MOSFET is a NMOS or PMOS.
5. (Currently Amended) The structure of claim 1, wherein the gate electrode ~~dielectric layer~~ comprises Al, Pt, TaN, TiN, or any metal gate electrode ~~dielectric~~.

6. (Currently Amended) The structure of claim 1, wherein the gate electrode ~~polysilicon layer~~ comprises polysilicon and poly-SiGe.

7. (Currently Amended) The structure of claim 5, wherein the gate electrode ~~polysilicon layer~~ comprises n-type or p-type dopants.

8. (Original) The structure of claim 1, wherein the substrate comprises n-type and p-type doped Ge, III-V group semiconductor, or silicon-on-insulator (SOI).

9. (Withdrawn - Currently Amended) A method of strained silicon carbon alloy MOSFET fabrication, comprising the steps of:

forming a graded SiGe layer on a substrate;

forming a relaxed buffer layer on the graded SiGe layer;

forming a strained silicon carbon alloy layer on the relaxed buffer layer acting as a channel;

forming an gate dielectric layer on the strained silicon carbon alloy layer;

forming a gate ~~polysilicon~~ layer on the gate dielectric layer;

etching the gate dielectric layer and the gate ~~polysilicon~~ layer to form a ~~polysilicon~~ gate electrode with a sidewall spacer; and

forming a source/~~drain~~ region and a drain region on the substrate opposite and adjacent to the polysilicon gate electrode.

10. (Withdrawn) The method of claim 9, wherein the relaxed buffer layer comprises Si-Ge-C alloy, Si, Ge or other combinations of at least two semiconductor materials.

11. (Withdrawn) The method of claim 9, wherein the gate dielectric layer comprises HfO_2 , Si_3N_4 , Al_2O_3 , or any high dielectric constant (high k) dielectric material.

12. (Withdrawn) The method of claim 9, wherein the MOSFET is a NMOS or PMOS.

13. (Withdrawn - Currently Amended) The structure of claim 9, wherein the gate electrode dielectric layer comprises Al, Pt, TaN, TiN, or any metal gate electrode dielectric.

14. (Withdrawn - Currently Amended) The method of claim 9, wherein the gate electrode polysilicon layer comprises polysilicon and poly-SiGe.

15. (Withdrawn - Currently Amended) The method of claim 14, wherein the gate electrode polysilicon layer comprises n-type or p-type dopants.

16. (Withdrawn) The method of claim 9, wherein the substrate comprises n-type and p-type doped Ge, III-II group semiconductor, or silicon-on-insulator (SOI).